

DS-QAE0A60G1-VB
60 W Analog Amplifier

- Support four types of audio input: Bluetooth, USB flash drive, microphone, and RCA, with flexible and convenient operation
- Built-in Bluetooth module, support fast Bluetooth playback
- Support plugging in the USB flash drive to play audio sources
- Support independent microphone volume control and two-channel partition volume control
- Support two-channel audio mixing output
- Adopt high-strength engineering plastics, sturdy and durable
- Integrated functional design, convenient and reliable

▪ Specification


| Function | |
|-----------------------|--|
| Protection Function | short circuit protection, overcurrent protection, over temperature protection, anti-static electricity protection, surge protection, electrical shock protection |
| Audio | |
| Rated Power | 60 W 24 VDC |
| Frequency Response | USB, Bluetooth: 20 Hz to 20 kHz MIC, RCA Input: 20 Hz to 8 kHz |
| THD and SNR | THD: ≤1% SNR: ≥100 dB |
| Interface | |
| Audio In | MIC 1: -20 dBV, 4 K Ω , unbalance, 6.35 mm jack USB 2.0 × 1 RCA in 1: 0 dBV, 5 K Ω , unbalance, RCA pin jack Bluetooth |
| Audio Out | Constant Voltage Output × 2 , 100 V COM Constant Resistance Output × 2 , 30 W 4 Ω to 8 Ω RCA Out 1: 0 dBV, 100 Ω , unbalance, RCA pin jack RCA Cascading: support a cascade of up to 3 amplifiers Bluetooth |
| LED Indicator | Power indicator (solid white): the device is normally working USB flash drive indicator (solid white): the device is in USB mode Bluetooth indicator (solid blue): the device is in Bluetooth mode USB flash drive indicator (off) and Bluetooth indicator (off): the MIC input and RCA input are mixed |
| Volume Knob | MIC Volume Knob × 1 , Partition 1 Volume Knob × 1 , Partition 2 Volume Knob × 1 |
| USB | USB 2.0 File format: FAT32 USB flash drive file playing logic: traverse play level 3 directory files in the USB flash drive. |
| Power Interface | Aperture size: \varnothing 2.0 mm |
| General | |
| Material | Plastic |
| Dimension | 190.8 mm × 230.8 mm × 51.2 mm (7.48" × 9.06" × 2.01") |
| Package Dimension | 362 mm × 280 mm × 100 mm (14.25" × 11.02" × 3.94") |
| Weight | Approx. 1445.5 g (3.19 lb.) |
| With Package Weight | Approx. 2113.3 g (4.66 lb.) |
| Color | White |
| Packing List | Device × 1 Power Adapter × 1 Power Cord × 1 Regulatory Compliance and Safety Information × 1 |
| Bluetooth | Bluetooth 5.3 , 10 m |
| Operating Temperature | -10 °C to 55 °C(14 °F to 131 °F) |

| | |
|--------------------|--|
| Operating Humidity | < 90% (No condensation) |
| Power Consumption | Standby Consumption: 1 W Annual Average Consumption: Max. Working Consumption: 60 W (based on the average playing time) |

▪ **Available Model**

DS-QAE0A60G1-VB

▪ **Dimension**



See Far, Go Further



www.hikvision.com
support@hikvision.com

